

1. PRODUCT AND COMPANY IDENTIFICATION

Company

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Functional Additives

Customer Service Telephone Number: (800) 331-7654
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)
Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: LUPEROX® 26M50
Synonyms: Peroxyesters, t-butyl peroctoate; t-butylperoxy 2-ethylhexanoate
Molecular formula: Complex Mixture
Chemical family: Organic peroxide - peroxyesters
Product use: Initiator

2. HAZARDS IDENTIFICATION

Emergency Overview

Color: Clear - colourless
Physical state: liquid
Odor: sweet

*Classification of the substance or mixture:

Flammable liquid., Category 3, H226
Organic peroxides, Type E, H242
Skin sensitisation, Category 1, H317
Specific target organ toxicity - single exposure, Category 3, H336
Aspiration hazard, Category 1, H304
Acute aquatic toxicity, Category 1, H400
Chronic aquatic toxicity, Category 2, H411

*For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms:



Signal word:

Danger**Hazard statements:**

H226 : Flammable liquid and vapour.
H242 : Heating may cause a fire.
H304 : May be fatal if swallowed and enters airways.
H317 : May cause an allergic skin reaction.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements:

Organic peroxide. Hazardous decomposition may occur. Temperature controlled. Thermally unstable - refrigeration required.

Precautionary statements:**Prevention:**

P210 : Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220 : Keep/Store away from clothing/ combustible materials.
P233 : Keep container tightly closed.
P234 : Keep only in original container.
P240 : Ground/bond container and receiving equipment.
P241 : Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 : Use only non-sparking tools.
P243 : Take precautionary measures against static discharge.
P261 : Avoid breathing gas/mist/vapours/spray.
P271 : Use only outdoors or in a well-ventilated area.
P272 : Contaminated work clothing should not be allowed out of the workplace.
P273 : Avoid release to the environment.
P280 : Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 : IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 : Call a POISON CENTER or doctor/ physician if you feel unwell.
P331 : Do NOT induce vomiting.
P333 + P313 : If skin irritation or rash occurs: Get medical advice/ attention.
P363 : Wash contaminated clothing before reuse.
P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P391 : Collect spillage.

Storage:

P403 + P233 : Store in a well-ventilated place. Keep container tightly closed.
P405 : Store locked up.
P410 : Protect from sunlight.
P411 + P235 : Maximum storage temperature is specified on label and in section 7 of SDS. Keep cool.
P420 : Store away from other materials.

Disposal:

P501 : Dispose of contents/ container to an approved waste disposal plant.

Supplemental information:**Potential Health Effects:**

Prolonged or repeated skin contact may cause defatting resulting in drying, redness and rash. Symptoms of aspiration may include increased breathing and heart rate, coughing and related signs of respiratory distress. May also cause: chest discomfort, accumulation of fluid in the lungs, (severity of effects depends on extent of exposure).

Medical conditions aggravated by overexposure:

Skin disorders.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Hexaneperoxoic acid, 2-ethyl-, 1,1-dimethylethyl ester	3006-82-4	>= 50 - < 52 %	H317, H400, H411, H242
Naphtha (petroleum), hydrotreated heavy	64742-48-9	< 50 %	H315, H411, H336, H304, H224
Naphtha (petroleum), heavy alkylate	64741-65-7	< 50 %	H226, H304, H413

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin:

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention if symptoms occur. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

Immediately flush eye(s) with plenty of water.

Ingestion:

If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Call a physician or Poison Control Center immediately. If vomiting occurs, have person lean forward. Never give anything by mouth to an unconscious person.

5. FIREFIGHTING MEASURES

Extinguishing media (suitable):

Water spray, Foam, Dry chemical

Extinguishing media (unsuitable):

Water may be ineffective., Do not use a solid water stream as it may scatter and spread fire.

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fight fire with large amounts of water from a safe distance.
Cool closed containers exposed to fire with water spray.
Closed containers of this material may explode when subjected to heat from surrounding fire.
After a fire, wait until the material has cooled to room temperature before initiating clean-up activities.
Do not allow run-off from fire fighting to enter drains or water courses.
Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, and other flames and ignition sources at locations distant from material handling point.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel. Ventilate the area. Eliminate all ignition sources. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as sodium bicarbonate, sodium carbonate, calcium carbonate, clean sand or non-acidic clay and then wet down (dampen) the mixture with water. DO NOT USE peat moss. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

7. HANDLING AND STORAGE

Handling**General information on handling:**

Temperature controlled! Cool and maintain proper temperature for product.
Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.
Do not taste or swallow.
Avoid contact with skin, eyes and clothing.
Avoid breathing vapor or mist.
Keep away from heat, sparks and flames.
No smoking.
Use only with adequate ventilation.
Wash thoroughly after handling.
Prevent product contamination.
Keep container tightly closed and away from combustible materials.
Keep only in the original container.
Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.
Container hazardous when empty.
Follow label warnings even after container is emptied.
RESIDUAL VAPORS MAY EXPLODE ON IGNITION.
DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.
Do not reuse container as it may retain hazardous product residue.
Improper disposal or reuse of this container may be dangerous and/or illegal.

Storage**General information on storage conditions:**

Keep refrigerated. Store in tightly closed container. Keep away from direct sunlight. Keep container closed when not in use. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Outside or detached storage is preferred. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Store out of direct sunlight in a cool well-ventilated place. Store in original container. Store away from combustibles and materials to avoid. Refer also to National Fire Protection Association (NFPA) Code 400, Hazardous Materials Code. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal, state and local regulations and National Fire Protection Association (NFPA) Codes which pertain to the specific local conditions of storage and use, including OSHA 29 CFR 1910.106 and NFPA 30, 70, 77, and 497.

Storage stability – Remarks:

Keep refrigerated. Follow the recommended storage temperatures provided in this Section in order to maintain stability and oxygen content.

Storage incompatibility – General:

Store separate from:

Strong acids

Strong bases

Strong oxidizing agents

Reducing agents

Accelerators

Amines

Friedel - Crafts reaction catalyst

transition metal salts

metal ions

Brass

Copper

Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Temperature tolerance – Do not store above:

59 °F (15 °C)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems.

Respiratory protection:

Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Wear chemical goggles, a face shield, and chemical resistant clothing such as a rubber apron when splashing may occur. Rinse immediately if skin is contaminated. Remove contaminated clothing immediately and wash before reuse. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where there is potential for eye contact, wear a face shield, chemical goggles, and have eye flushing equipment immediately available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear - colourless
Physical state:	liquid
Odor:	sweet
Odor threshold:	No data available
Flash point	The flashpoint of this product is greater than the Self Acceleration Decomposition Temperature (SADT).
Auto-ignition temperature:	No data available
Lower flammable limit (LFL):	No data available
Upper flammable limit (UFL):	No data available
pH:	No data available
Density:	0.83 g/cm ³ (68 °F (20 °C))
Specific Gravity (Relative density):	0.83 (68 °F (20 °C))Water=1 (liquid)
Vapor pressure:	3.7 mmHg (40.01 °F (4.45 °C))
Vapor density:	No data available
Boiling point/boiling range:	Decomposes before boiling. Rate of decomposition increases with rising temperature.
Melting point/range:	< -40 °F (< -40 °C)
Freezing point:	< -40 °F (< -40 °C)
Evaporation rate:	No data available
Solubility in water:	insoluble
Viscosity, dynamic:	No data available
Oil/water partition coefficient:	No data available

**Self-Accelerating
Decomposition
Temperature (SADT):** 129 °F (54 °C) 35 pound container

Thermal decomposition No data available

Active oxygen content: 3.70 - 3.85 %

Flammability: See GHS Classification in Section 2

10. STABILITY AND REACTIVITY

Stability:

This material is chemically unstable and should only be handled under specified conditions. See HANDLING AND STORAGE section of this SDS for specified conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

Strong acids
Strong bases
Strong oxidizing agents
Reducing agents
Accelerators
Friedel - Crafts reaction catalyst
transition metal salts
metal ions
Brass
Copper
Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Conditions / hazards to avoid:

See HANDLING AND STORAGE section of this SDS for specified conditions. SADT - Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. This reaction will generate flammable vapors which may autoignite. The length of time to generate a decomposition reaction, after the SADT has been reached or exceeded, is dependent upon how much the SADT has been exceeded and the length of time needed for the reaction exotherm (heat spike from increasing decomposition rate) to initiate a rapid decomposition reaction. Typically, SADT is inversely proportional to package size. Larger packages will have a lower SADT due to smaller ratio to heat transfer area to volume of product.

Hazardous decomposition products:

Temperatures at or above SADT can result in the release of hazardous decomposition products which are flammable and may autoignite.

Thermal decomposition giving flammable and toxic products:

Carbon oxides
Hazardous organic compounds

11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for Hexaneperoxoic acid, 2-ethyl-, 1,1-dimethylethyl ester (3006-82-4)**Acute toxicity****Oral:**

Practically nontoxic. (rat) LD₀ > 10,000 mg/kg.

Dermal:

Practically nontoxic. (rabbit) LD₅₀ = 16,800 mg/kg.

Inhalation:

Practically nontoxic. (rat) 4 h LC₅₀ = 42.2 mg/l. (aerosol)

Skin Irritation:

Practically non-irritating. (rabbit) Irritation Index: 1.2/8.0. (4 h) (occluded exposure)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

May cause an allergic skin reaction. Buehler method. (guinea pig) Skin allergy was observed.

Repeated dose toxicity

Subchronic oral administration to rat / No adverse effects reported.

Repeated oral administration to rat / affected organ(s): kidney, liver / signs: changes in organ structure or function, changes in blood cell counts, clinical chemistry changes

Genotoxicity**Assessment in Vitro:**

Both positive and negative responses for genetic changes were observed in laboratory tests using: bacteria

Genetic changes were observed in laboratory tests using: animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in a laboratory test using: mice

An equivocal response has been reported in a test using: mice

Developmental toxicity

Exposure during pregnancy. Oral (rat) / delays in development

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction.

Data for Naphtha (petroleum), hydrotreated heavy (64742-48-9)**Acute toxicity****Oral:**

No deaths occurred. (rat) LD0 > 5,000 mg/kg.

Dermal:

May be harmful in contact with skin. (rabbit) LD50 > 2,000 mg/kg.

Inhalation:

No deaths occurred. (rat) 4 h LC0 > 5 mg/l. (vapour)

Specific target organ toxicity - single exposure:

May cause drowsiness or dizziness. (central nervous system)

Skin Irritation:

Causes skin irritation. (rabbit)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Repeated skin exposure. (guinea pig) No skin allergy was observed (data for a similar material)

Repeated dose toxicity

Subchronic inhalation administration to rat / affected organ(s): kidney / signs: changes in organ weights, changes in organ structure or function, hyaline droplet nephropathy / (not considered relevant in humans)

Repeated oral administration to rat / affected organ(s): kidney / signs: changes in organ weights, changes in organ structure or function, hyaline droplet nephropathy / (not considered relevant in humans)

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: mice

Developmental toxicity

Exposure during pregnancy. Inhalation (rat) / No birth defects were observed.

Other information

LUPEROX® 26M50

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Aspiration hazard

May be fatal if swallowed and enters airways.

Human experience**Inhalation:**

Cardio-vascular system: Irregular cardiac activity, rapid heart beat. (repeated or prolonged exposure) (effects associated with substance abuse) (data for similar materials)

Human experience**Skin contact:**

Skin: No skin allergy was observed. (studied using human volunteers) Prolonged skin contact may defat the skin and produce dermatitis.

Data for Naptha (petroleum), heavy alkylate (64741-65-7)**Acute toxicity****Oral:**

Practically nontoxic. (rat) LD50 > 7,600 mg/kg.

Dermal:

No deaths occurred. (rabbit) LD0 > 3,040 mg/kg.

Inhalation:

No deaths occurred. (rat) 4 h LC0 > 9.3 mg/l. (saturated vapor)

Skin Irritation:

Causes mild skin irritation. (rabbit) Irritation Index: 2.4/8.0. (4 h)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. (guinea pig) No skin allergy was observed

Repeated dose toxicity

Repeated inhalation administration to rat / affected organ(s): kidney / signs: damage, changes in organ structure or function, hyaline droplet nephropathy / (not considered relevant in humans)

Other information

The information presented is from representative materials in this chemical class. The results may vary depending on the test substance.

Aspiration hazard

May be fatal if swallowed and enters airways.

Human experience**Inhalation:**

Cardio-vascular system: Irregular cardiac activity, rapid heart beat. (repeated or prolonged exposure) (effects associated with substance abuse) (data for similar materials)

Human experience**Skin contact:**

Skin: Prolonged skin contact may defat the skin and produce dermatitis.

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

Data for Hexaneperoxoic acid, 2-ethyl-, 1,1-dimethylethyl ester (3006-82-4)**Biodegradation:**

Inherently biodegradable. (28 d) biodegradation 55 %

Octanol Water Partition Coefficient:

log Pow = 4.79

Data for Naphtha (petroleum), hydrotreated heavy (64742-48-9)**Biodegradation:**

Readily biodegradable. (28 d) biodegradation 77 %

Octanol Water Partition Coefficient:

log Pow = 2.1 - 6.5 (calculated)

Data for Naphtha (petroleum), heavy alkylate (64741-65-7)**Biodegradation:**

Not readily biodegradable. (28 d) biodegradation 8 - 22 %

Potential to bioaccumulate

Octanol Water Partition Coefficient:

log Pow = 2.8 - 6 (calculated) (data for a similar material)

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for Hexaneperoxoic acid, 2-ethyl-, 1,1-dimethylethyl ester (3006-82-4)**Aquatic toxicity data:**

Toxic. *Poecilia reticulata* (guppy) 96 h LC50 = 8.6 mg/l

Aquatic invertebrates:

Toxic. *Daphnia magna* (Water flea) 48 h EC50 = 7.5 mg/l

Algae:

Very toxic. *Pseudokirchneriella subcapitata* (green algae) 72 h ErC50 = 0.4394 mg/l

Microorganisms:

Respiration inhibition / Activated sludge 30 min EC50 = 64 mg/l

Chronic toxicity to aquatic invertebrates:

Toxic. *Pseudokirchneriella subcapitata* 21 d NOEC r = 0.45 mg/l

Chronic toxicity to aquatic plants:

Pseudokirchneriella subcapitata (green algae) 72 h NOEC (growth rate) = 0.018 mg/l

Data for Naphtha (petroleum), hydrotreated heavy (64742-48-9)**Aquatic toxicity data:**

Toxic. Pimephales promelas (fathead minnow) 96 h LL50 = 8.2 mg/l

Aquatic invertebrates:

Toxic. Daphnia magna (Water flea) 48 h EL50 = 4.5 mg/l (nominal concentrations reported, Water accommodated fraction was tested.)

Algae:

Toxic. Pseudokirchneriella subcapitata (green algae) 72 h EL50 = 3.1 mg/l (nominal concentrations reported, Water accommodated fraction was tested.)

Chronic toxicity to aquatic invertebrates:

Daphnia magna (Water flea) 21 d NOEC (reproduction) = 2.6 mg/l (Water accommodated fraction was tested.) (Nominal concentration)

Data for Naphtha (petroleum), heavy alkylate (64741-65-7)**Aquatic toxicity data:**

No effect up to the limit of solubility. Fish 96 h LL50 > 1,000 mg/l

No effect up to the limit of solubility. Carassius auratus (goldfish) 24 h

Aquatic invertebrates:

No effect up to the limit of solubility. Daphnia magna (Water flea) 48 h EL50 > 1,000 mg/l

Algae:

No effect up to the limit of solubility. Algae 72 h EL50 > 1,000 mg/l

13. DISPOSAL CONSIDERATIONS**Waste disposal:**

Dilution followed by incineration is the preferred method. Dilution ratio of 10:1 in a clean, compatible, combustible solvent (i.e., Fuel Oil #2, mineral oil) will reduce reactivity hazard during incineration and transportation. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

Take appropriate measures to prevent release to the environment.

14. TRANSPORT INFORMATION**US Department of Transportation (DOT)**

UN Number	:	3117
Proper shipping name	:	Organic peroxide type E, liquid, temperature controlled
Technical name	:	(Tert-Butylperoxy-2-ethylhexanoate, >32-52%)
Class	:	5.2

Packaging group : II
 Marine pollutant : yes
 Control temperature : 86 °F (30 °C)
 Emergency temperature : 95 °F (35 °C)

International Maritime Dangerous Goods Code (IMDG)

UN Number : 3117
 Proper shipping name : ORGANIC PEROXIDE TYPE E, LIQUID, TEMPERATURE CONTROLLED
 Technical name : (Tert-BUTYL PEROXY-2-ETHYLHEXANOATE, >32-52%)
 Class : 5.2
 Marine pollutant : yes
 Control temperature : 86 °F (30 °C)
 Emergency temperature : 95 °F (35 °C)

15. REGULATORY INFORMATION

Chemical Inventory Status

EU. EINECS	EINECS	Conforms to
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Conforms to

United States – Federal Regulations

SARA Title III – Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

SARA Title III - Section 311/312 Hazard Categories:

Acute Health Hazard, Fire Hazard, Reactivity Hazard

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

United States – State Regulations**New Jersey Right to Know**

No components are subject to the New Jersey Right to Know Act.

Pennsylvania Right to Know

<u>Chemical Name</u>	<u>CAS-No.</u>
Hexaneperoxoic acid, 2-ethyl-, 1,1-dimethylethyl ester	3006-82-4
Naphtha (petroleum), hydrotreated heavy	64742-48-9
Naphtha (petroleum), heavy alkylate	64741-65-7

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

16. OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Miscellaneous:

LUPEROX® 26M50

Other information: Back-up or emergency refrigeration should be available in case primary refrigeration is lost. Emergency dry ice source(s) should be known in case of refrigeration failure. Temperature in storage areas should be monitored. Refrigeration systems should have high temperature alarms to warn of loss of refrigeration. Refer to National Fire Protection Association (NFPA) Codes 30, 70, 77, and 497 for safe handling.

Latest Revision(s):

Reference number: 000000034077
Date of Revision: 10/18/2015
Date Printed: 11/29/2016

LUPEROX® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices. It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.